

SPECIFICATIONS

Page 1 of 2

ITEM NO.	DESCRIPTION	CHECK ✓ IF AS SPECIFIED	DESCRIBE FULLY IF NOT AS SPECIFIED
1.	Kettle, Gas Fired, 2/3 Steam Jacketed, Cleveland model KGL-60 or equal		
	Capacity 60 gallons / 225 liters		
	LP gas operation		
	Electronic Ignition		
	High efficiency Power Burner Heating System (62% to 65% efficiency)		
	Fast Heat-up and Recovery Time, 190M BTU's at 60 gallons		
	Insulated Heat Exchanger		
	Automatic Ignition System		
	Steam Jacket permanently filled with treated, distilled water. Venting and/or refilling not required		
	Jacket water fill and sight glass		
	Solid State Controls, for Temperature and Low Water Safety, in a plug-in Control Module		
	Control Panel includes: Precise, consistent temperature control: less than $\pm 1^{\circ}\text{C}$ variance, L.E.D. Indicators for Heat Cycle and Low Water Warning as well as Power "on/off" Switch.		
	Front mounted combination Pressure/Vacuum Gauge, Pressure Relief Valve and Air Eliminator Valve		
	Type 304 Stainless Steel with #4 finish on kettle and supports		
	316 stainless steel liner		
	Kettle gallon markings		
	3" diameter Tangent Draw-Off Valve with Drain Strainer		
	DC3 Strainer for Cleveland		
	DS3S solid drain cover, 3" draw off		
	Support Legs with level adjustable feet, flanged for floor bolting		
	Spring-assisted, hinged, rotate-able, domed Stainless Steel Cover		
	50 psi Steam Jacket Rating and Safety Valve		

SPECIFICATIONS

Page 2 of 2

	30 psi operating pressure		
	Standard voltage is 120 volts, 60 Hz, single-phase, supplied with cord and plug		
	Faucet Mounting Bracket (FBK)		
	SPKS single pantry faucet w/swing spout		
	Stainless Steel Bar Cover		
	Correctional Package to include:		
	Tamper Resistant Spring Assist Cover, Tamper proof screws, Anti rotational bracket welded to cover		
	Heavy Duty Reinforced Rim Bar: ½ X 1" stainless steel bar continuously welded around the rim		
	Tangent Draw-Off Valve Modification, valve will be modified by having the valve handle fastened to stem with tamper proof screws.		
	Non removable, reinforced faucet bracket.		
	Standard screws replaced by tamper proof screws for fastening all removable covers and panels.		
	Set of Screwdrivers: For tamper proof screws.		
	Protective Box for Controls: Completely covers controls		
	Pressure Gauge Guard: ¼" x ½" stainless steel bar bolted over gauge.		
	To include operator, service and parts manuals		
	Warranty-at least one year parts and labor		